

Sustainability data sheet

ARDEX SN

Flexible Sealant for use in Tile Movement Joints

ARDEX SN is an acetoxy curing silicone for applications such as movement joints (between tiles), internal corners (tiled wall and floor) and connecting joints between tiled surface and benchtops, bath edges, cupboards, splashbacks.

Emissions

According GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf) -

According French VOC Classification

A+



solvent-free

EPD (Environmental Product Declaration)

ARDEX SN corresponds to FEICA EPD:

EPD-DBC-20220180-IBF1

According BASTA

ARDEX SN is BASTA registered.

BASTA registration means that we can verify that this product meets agreed properties criteria regarding properties hazardous to the environment and health. See www.bastaonline.se



Technical Assessment

According GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):
GISCODE -

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de



ARDEX SE

Flexible Sealant for use in Tile Movement Joints

Sustainable Building

Accordinging DGNB (German Sustainable Building Council)

Version 2023

DGNB criteria ENV 1.2: Local environmental impact

ARDEX SN can be categorized under Indoor bonding and waterproofing. ARDEX SN has no GISCODE and does not meet the requirements according EMICODE® based on GEV.

ARDEX SE does not fulfil the requirements for DGNB.

Accordinging LEED (Leadership in Energy and Environmental Design)

Version 4 (2014)

EQ: Low Emitting Materials

ARDEX SN does not meet the requirements according EMICODE® based on GEV which are accepted by LEED.

ARDEX SN does not meet the requirements.

MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX SN corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate“.

ARDEX SN fulfils the requirements and contributes to achieving a LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.

Version 2009

IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

The permitted limit value in the category 'Architectural Sealant' according SCAQMD Rule 1168 is 250 g/L. The VOC value of ARDEX SN according SCAQMD Rule 1168 is < 250 g/L.

ARDEX SN meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.

MR Credit 5.1 und 5.2: Regional Materials

Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

Accordinging BREEAM-NOR (Building Research Establishment Environmental Assessment Methodology)

Version 2016

BREEAM-NOR criteria Hea 02 Indoor air quality

ARDEX SN does not fulfil the required emission limits.

ARDEX SN does not meet the requirements according BREEAM-NOR.

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de



ARDEX SE

Flexible Sealant for use in Tile Movement Joints

Accordinging Nordic Swan Ecolabelling

ARDEX SN is not listed in the database for building products that can be used in Nordic Swan Eco labelled buildings.

Notice: This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship. Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH
Witten, 08/07/2024

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de

